

FCA CANADA

2019 Dodge Grand Caravan

SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in millimetres (inches) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Multipurpose vehicle
Assembly Plant	Windsor, Ontario
EnerGuide Vehicle Class	Multipurpose vehicle
Introduction Date	December 2008 as a 2009 model

BODY AND CHASSIS

Layout	Transverse front engine, front-wheel drive
Construction	Unitized steel with hinged front doors; Sliding left- and right-side doors — power available Rear liftgate with gas props — power available

ENGINE: 3.6-LITRE PENTASTAR, GASOLINE, V-6

Availability	Standard
Type and Description	60-degree bank angle, liquid-cooled with three-plenum intake manifold, electronically controlled manifold tuning valve and short-runner valves
Displacement	3,605 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 (3.78 x 3.23)
Valve System	DOHC, 24 valves, hydraulic, roller finger followers
Fuel Injection	Sequential, multiport, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mold A319 aluminum heads
Compression Ratio	10.2:1
Power (SAE net)	283 hp (211 kW) @ 6,400 rpm
Torque (SAE net)	260 lb.-ft. (353 N•m) @ 4,400 rpm
Max. Engine Speed	6,800 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2 — acceptable

Oil Capacity	5.67 litres (6 quarts) with filter
Coolant Capacity	9.75 litres (10.3 quarts)
Emission Controls	Dual catalytic converter, four heated oxygen sensors, electronic EGR and internal engine features ^(a)
EnerGuide (2018) Fuel Consumption Ratings L/100 km (MPG – imp. gal.)	13.7(21)/9.4(30)/11.8(24)
Assembly Plant	Trenton Engine Plant, Trenton, Michigan

Based on 2018 EnerGuide fuel consumption ratings. Government of Canada test methods used. Your actual fuel consumption will vary based on driving habits and other factors. For EnerGuide information, please visit the Government of Canada website: www.vehicles.nrcan.gc.ca

TRANSMISSION: 62TE, AUTOMATIC, SIX-SPEED OVERDRIVE

Availability	Standard
Description	Six-speed, adaptive electronic control, electronically modulated torque converter clutch
Gear Ratios	
1st	3.90
2nd	2.69
3rd	2.16
4th	Upshift — 1.37 WOT kickdown — 1.49
5th	0.95
6th	0.65
Reverse	3.04
Transfer Ratio	0.95
Final Drive Ratio	3.16
Overall Top Gear	2.068

ELECTRICAL SYSTEM

Alternator	160-amp
Battery	730 CCA, maintenance-free

SUSPENSION

Front	Independent MacPherson strut, coil over gas-charged shock absorbers, stabilizer bar with isolated suspension cradle
-------	---

Rear	Twist-beam axle with coil springs, track bar, gas-charged shock absorbers; self-leveling shock absorbers optional
------	---

STEERING

Type	Power rack and pinion
Overall Ratio	14.3:1
Turning Diameter (curb-to-curb)	11.92 m (39.1 ft.)
Steering Turns (lock-to-lock)	2.90
Power Steering Pump	Hydraulic

BRAKES

Type	All — Power assist, 230 x 230 (9 x 9) tandem-diaphragm vacuum, anti-lock brake system
Availability	Standard on all models
Front	
Rotor Size and Type	330 x 28 (13.0 x 1.1) vented rotor
Caliper Size and Type	51 (2.0) twin-piston
Swept Area	475 sq. cm (73.6 sq. in.)
Rear	
Rotor Size and Type	328 x 12 (12.9 x 0.47) solid rotor
Caliper Size and Type	45 (1.8) single-piston integral parking brake
Swept Area	429 sq. cm (66.5 sq. in.)

DIMENSIONS AND CAPACITIES

Wheelbase	3,078.2 (121.2)
Overhang — Front	960.9 (37.8)
Overhang — Rear	1,112.1 (43.8)
Track — Front	1,665.5 (65.6)
Track — Rear	1,647.0 (64.8)
Overall Length	5,174 (203.7)
Overall Width	1,998.2 (78.7)
Overall Width With Mirrors	2,246.8 (88.5)

Overall Height	1,752.6 (69.0)
Liftover Height	609.0 (24.0)
Cargo Width at Wheelhouse	1,236.0 (48.8)
Maximum Cargo Height	1,172.4 (46.16)
Approach Angle (degrees)	13.7
Ramp Breakover Angle (degrees)	13.6
Departure Angle (degrees)	18.5
Minimum Running Ground Clearance (curb load)	148 (5.8)
Frontal Area	32.3
Drag Coefficient (Cd)	.316
Aero CdA	10.2
Fuel Tank Capacity, litres (gallons)	76 (20)
Gross Vehicle Weight Rating (GVWR), kg (lbs.)	2,744.2 (6,050)
Towing Capacity, kg (lbs).	1,632.9 (3,600) — with Trailer-tow Prep Package
U.S. Curb Weight, kg (lbs.)	2,050 (4,510)
Weight Distribution % F/R	56/44

ACCOMMODATIONS

Seating Capacity (front/second/third rows)	2/2/3
Front	
Headroom	1,011.9 (39.8)
Legroom	1,034.4 (40.7)
Shoulder Room	1,618.6 (63.7)
Hip Room	1,484.5 (58.4)
Seat Travel	220 (8.7)
Recliner Angle Range (degrees)	Manual recline: 88 Power recline: 59
Front Passenger Volume, L (cu. ft.)	1654 (58.4)
Intermediate	
Headroom	938.5 (37.0) bench seat 998.9 (39.3) captain's chairs

Legroom	941.1 (37.1) bench seat
	925.9 (36.5) captain's chairs
Shoulder Room	1643.3 (64.7) bench seat
	1628.1 (64.1) captain's chairs
Hip Room	1,646 (64.8) bench seat
	1,650.8 (65.0) captain's chairs
Intermediate Passenger Volume, L (cu. ft.)	1529 (54.0)
Rear	
Headroom	962.9 (37.9) bench seat/captain's chairs
Legroom	958.5 (37.7) bench seat
	829.7 (32.7) captain's chairs
Shoulder Room	1,574.6 (62.0) bench seat/captain's chairs
Hip Room	1,237.7 (48.7) bench seat/captain's chairs
Rear Passenger Volume, L (cu. ft.)	1447 (51.1)
Cargo Volume	
Maximum Passenger Volume, L (cu. ft.)	4491 (158.6)
Maximum SAE Volume Behind First Row, L (cu. ft.)	3973 (140.3)
Maximum SAE Volume Behind Second Row, L (cu. ft.)	2234 (78.9)
Maximum SAE Volume Behind Third Row, L (cu. ft.)	881 (31.1)
Total Passenger Plus Volume Behind Third Row, L (cu. ft.)	5401 (190.8)

WHEELS

Availability	Standard — Grand Caravan CVP, SXT
Type and Material	Steel with painted bolt-on wheel cover
Size	17 x 6.5
Availability	Standard —CVP
	Optional — SE Plus Group
Type and Material	Cast-aluminum, 5-spoke
Size	17 x 6.5
Availability	Optional — SXT with SXT Plus Group

Type and Material	Machined cast-aluminum, 10-spoke Tech Silver
Size	17 x 6.5
Availability	Standard — SXT Premium Plus
Type and Material	Polished aluminum, 10-spoke with Granite Crystal pockets
Size	17 x 6.5
Availability	Standard — Crew, Crew Plus
Type and Material	Painted aluminum, twin five-spoke
Size	17 x 6.5
Availability	Standard —GT Optional — SXT with Blacktop Package
Type and Material	Polished aluminum, 10-spoke with Gloss Black Pockets
Size	17 x 6.5
TIRES	
Availability	Standard — Grand Caravan CVP, SXT, SXT Premium Plus, Crew, Crew Plus
Size and Type	225/65R17, BSW Touring
Model	Yokohama Brand tires
Availability	Standard — Grand Caravan GT
Size and Type	225/65R17, BSW All-season
Model	Michelin Brand Tires
Parking Brake Type	Integral parking brake
Four-wheel Anti-lock Brakes	Standard
Electronic Stability Control	Standard
All-speed Traction Control	Standard
Brake Assist	Standard

• END •