

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2008 Dodge Ram 3500 Chassis Cab

FEATURE AVAILABILITY

	ST	SLT	Laramie
EXTERIOR			
Air Dam – black	S	S	S
Active Turn Signals	S	S	S
Badging			
SLT	—	S	—
Laramie	—	—	S
Bumper			
Front, gray	S	—	—
Front, bright	—	S	S
Cargo Lamp – with integrated center-high mounted stop lamp	O	O	O
Fascia			
Front, upper gray	S	S	S
Fog Lamps	—	O	S
Glass – tinted	S	S	S
Grille			
Dark gray surround, black billet grille	S	—	—
Chrome surround, black billet grille (included with ST Décor Group)	P	S	—
Chrome surround, chrome billet grille	—	—	S
Headlamps			
Halogen	S	S	S
Lamps			
Clearance	S	S	S
Mirrors			
Manual adjusting, trailer tow, black (7-inch x 10-inch)	S	—	—
Power, heated, trailer tow, black (7-inch x 10-inch)	—	S	S
Paint			
Monotone	S	S	S
Rear Window			
Fixed	S	S	—
Sliding	O	O	—
Power sliding	—	O	S

	ST	SLT	Laramie
Defroster	—	S	S
Skid Plate (covers transfer case on 4x4 only; included in Heavy Duty Snow Plow Prep Group)	P	P	S
Shield, front hood protection	O	O	O
Tow Hooks (standard on 4x4; optional on 4x2)	S/O	S/O	S/O
INTERIOR			
Air Conditioning	O	S	—
Manual dual-zone temperature control	—	—	S
Armrest, center	S	S	S
Assist Handle, passenger side	S	S	S
Bezel			
Lower center stack, black	S	—	—
Lower center stack, color-keyed	—	S	—
Lower center stack, Satin Silver II	—	—	S
Radio surround, Satin Silver II	—	S	—
Radio surround, wood grain	—	—	S
Cigar Lighter	S	S	S
Console			
Overhead with trip computer (when equipped with HEMI engine)	—	P	P
Overhead with trip computer and EVIC (included with turbodiesel engine)	P	P	P
Cup Holders			
Front, lower IP mounted (2) (with automatic transmission)	S	S	S
Front, floor console mounted (2) (with manual transmission)	S	S	S
Rear, floor-mounted (2) (Quad Cab; N/A on ST)	S	S	S
Dome Lamp	S	S	S
Floor Covering			
Heavy-duty vinyl	S	O	O
Carpet	O	S	S
Floor Mats			
Front and rear, carpeted (Quad Cab)	—	S	—
Front, carpeted (regular cab)	—	S	—
Luxury front	—	—	S
Rear	—	—	S
Heater only	S	—	—
Instrument Cluster with 120-mph speedometer, tachometer, odometer, engine hours meter, oil temperature, engine temperature, voltmeter, fuel level, and telltales	S	S	S
Insulation – Dash liner and floor tunnel	S	S	S
Load Floor (rear fold flat; Quad Cab)	—	P	S
Map Pocket – with power seats (driver side)	—	S	S
Mirrors			
Rearview manual day/night	S	S	—

	ST	SLT	Laramie
Automatic rearview dimming day/night (included with Light Group and UConnect®)	—	P	S
Illuminated visor – driver and passenger side (included in Light Group)	—	P	S
Pedals – power adjustable	—	O	S
Power Accessory Outlet – auxiliary 12-volt outlet in IP	S	S	S
Power Auxiliary Outlet – in center armrest/business console (included with premium features seat)	—	P	S
Radios			
AM/FM stereo with CD player	S	S	S
Radio delete	L	—	—
AM/FM/MP3 stereo with integrated six-disc CD changer and seven-speaker Infinity® system (included with Sun, Safe and Sound Package)	—	O/P	S
AM/FM/MP3 stereo with in-dash six-disc CD changer; integrated DVD-based Navigation System with 5.8-inch display screen and seven-speaker Infinity® system	—	O	O
AM/FM/MP3 stereo with cassette, integrated six-disc CD changer and seven-speaker Infinity® system	—	O	O
SIRIUS Satellite Radio (one year of service provided)	O	O	S
UConnect® Hands-free Communication System with auto-dimming rearview mirror	—	O/P	O
Seats			
Six-way power driver's with lumbar support	—	P	S
Power six-way driver and passenger (Quad Cab only)	—	—	S
Heated driver's and front passenger	—	—	S
Vinyl 40/20/40 split bench front seat with adjustable head restraints for outboard seating positions, driver and front-passenger recliners, and folding center armrest (Quad Cab models include folding rear bench seat trimmed in vinyl)	S	O	—
Cloth-trimmed 40/20/40 split-bench front seat features YES Essentials® seat fabric with adjustable head restraints for outboard seating positions, driver and front-passenger recliners and folding center armrest/business console (Quad Cab models include folding rear bench seat trimmed in cloth)	—	S	—
Leather-trimmed 40/20/40 split-bench front seat with adjustable head restraints for outboard seating positions, driver and front-passenger recliners, fold-flat load floor and folding center armrest/business console (Quad Cab models include 60/40 split-folding rear bench seat trimmed in vinyl)	—	—	S
Cloth-trimmed 40/20/40 split-bench front seat with adjustable head restraints for outboard seating positions, driver and front-passenger recliners and folding center armrest (Quad Cab models include folding rear bench seat)	O	—	—
Cloth-trimmed 40/20/40 premium split-bench front seat featuring YES Essentials® seat fabric with adjustable head restraints for outboard seating positions, six-way power driver's seat, driver and front-passenger recliners, fold-flat load floor and folding center armrest/business console (Quad Cab models include 60/40 split folding rear bench)	—	O	—
Cloth-trimmed, low-back bucket seats featuring YES Essentials® seat fabric with adjustable head restraints, driver and front-passenger recliners, fixed center console, and rear fold-flat floor (Quad Cab models include 60/40 split folding rear bench seat trimmed in cloth)	—	O	—
Leather-trimmed, low-back bucket seats featuring YES Essentials® seat fabric with adjustable head restraints, driver and front-passenger recliners, fixed center console, and rear fold-flat floor (Quad Cab models include 60/40 split folding rear bench seat trimmed in vinyl)	—	—	O
Speed Control	O	S	S

	ST	SLT	Laramie
Steering Column, tilt	S	S	S
Steering Wheel			
Four-spoke	S	S	—
Leather-wrapped	—	O	S
Steering wheel-mounted Audio Controls (must have AM/FM cassette/CD or AM/FM radio with CD and six-disc in-dash CD changer with Infinity® speaker system and leather-wrapped steering wheel)		O	S
Storage			
Front-seat center cushion	—	P	S
Front, behind seat (Regular Cab only)	S	S	S
Rear, under-seat compartment (Quad Cab only)	S	S	S
Sun Visors			
Front-passenger, with mirror	S	S	—
Driver and front-passenger with illuminated vanity mirrors (included with Light Group)	—	P	S
Windows			
Manual	S	—	—
Power front (and rear on Quad Cab) with driver's one-touch down (included with Power Accessory Group and Power & Remote Entry Group)	L	S	S
Windshield Wiper and Washer System – two-speed with variable-delay intermittent	S	S	S
POWERTRAIN AND CHASSIS			
5.7-liter HEMI® Magnum® V-8 with manual six-speed overdrive transmission	S	S	S
5.7-liter HEMI® Magnum® V-8 with five-speed automatic transmission	O	O	O
6.7-liter H.O. Turbo Diesel with manual six-speed overdrive transmission	O	O	O
6.7-liter H.O. Turbo Diesel with six-speed automatic transmission	O	O	O
Alternator			
136-amp	S	S	S
160-amp (included with Heavy-Duty Snow Plow Prep package)	P	P	P
220-amp (requires Cummins turbodiesel)	O	O	O
Axle			
Anti-spin rear differential	O	O	O
3.73 ratio (included with Cummins/Manual transmission combination only)	P	P	P
4.10 ratio (included with Cummins/Manual transmission combination only)	S/O	S/O	S/O
Battery			
750-amp (two standard with diesel engine)	S	S	S
Brakes			
Four-wheel disc, four-wheel anti-lock, power assist	S	S	S
Diesel exhaust brake (requires Cummins diesel)	S	S	S
Engine block heater	O/P	O/P	O/P
Engine Cooling, heavy-duty	S	S	S
Fuel Tank			

	ST	SLT	Laramie
52-gallons; rear-mounted	S	S	S
22-gallons; mid-mounted	O	O	O
Shock Absorbers			
Front, heavy-duty	S	S	S
Rear, heavy-duty	S	S	S
Stabilizer Bar, front and rear	S	S	S
Steering, power assisted, recirculating ball	S	S	S
Suspension			
Front – solid live axle with coil springs, four trailing links and heavy-duty shocks	S	S	S
Rear – longitudinal leaf springs with rear stabilizer bar and heavy-duty shocks	S	S	S
Tip Start (included with 5-speed automatic transmission)	O	O	O
Tires			
LT235/80R17E black sidewall (BSW) all-season	S	S	S
LT235/80R17E outline white letter (OWL) all-season (4x2 only; not available with Single Rear Wheel Group)	—	O	O
LT235/80R17E BSW on/off road (4x4 only; not available with Single Rear Wheel Group)	O	—	—
LT235/80R17E OWL on/off road (4x4 only; not available with Single Rear Wheel Group)	—	O	O
LT265/80R17E BSW all-season (included with Single Rear Wheel Group)	S	S	S
LT265/80R17E OWL all-season (60-inch CA 4x2 only; must have Single Rear Wheel Group)	—	O	O
LT265/80R17E OWL on/off road (60-inch CA 4x2 only; must have Single Rear Wheel Group)	—	O	O
Spare (full size with jack & tools)	O	O	O
Transfer Case			
Manual (4x4 models)	S	S	—
Electric shift (4x4 models)	—	O	S
Wheels			
17- by 7.5-inch argent steel (included with Single Rear Wheel Group)	S	—	—
17- by 8.0-inch chrome-clad steel (included with Single Rear Wheel Group)	—	P	—
17- by 8.0-inch polished forged aluminum (60-inch CA only; optional with Single Rear Wheel Group only)	—	O	—
17- by 6.0-inch steel with argent wheel skin	S	—	—
17- by 6.0-inch steel with chrome wheel skin	O	S	S
SAFETY AND SECURITY			
Brake-Park Interlock (w/automatic transmission)	S	S	S
Daytime Running Lamps	L	L	L
Door Locks			
Manual	S	—	—
Power (included with Power Accessory & Power and Remote Entry Groups)	P	—	—
Energy-absorbing steering column	S	S	S

	ST	SLT	Laramie
Enhanced Accident Response System (EARS)	S	S	S
Remote Keyless Entry (included with Power & Remote Entry Group)	L	S	S
Remote Start (must have HEMI engine & automatic transmission)	—	O	O
Restraints			
Front, next-generation multi-stage driver and passenger air bags(a)	S	S	S
Driver only (deletes Next-generation multi-stage front air bags)	O	O	—
Front/Rear height-adjustable three-point seat belts with traveling buckles, Constant Force Retractors (CFR), pretensioners and BeltAlert	S	S	S
Passenger air bag on/off switch(b)	S	S	S
LATCH (Lower Anchors and Tethers for CHildren)	S	S	S
Seat Belt Cluster Lamp (stays illuminated until driver buckles up)	S	S	S
Security Alarm	—	O	S
Sentry Key [®] engine immobilizer (included in Power & Remote Entry Package)	L	S	S
(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children 12 years and under.			
(b) Important, always remove key. Rearward-facing child seats may be used in the front seat only with the passenger air bag turned off.			

PACKAGES

Power Accessory Group – includes power windows; power door locks; and power heated exterior mirrors (fleet only)	L	—	—
Power and Remote Entry Group – includes power windows; power door locks; power and heated 7-inch x 10-inch exterior trailer tow mirrors; Remote Keyless Entry; and Sentry Key [®] anti-theft engine immobilizer (fleet only)	L	—	—
Power Take Off (PTO) Prep Group	O	O	O
Single Rear Wheel Group – includes 11.5-inch axle, 10,200 lb. GVWR, LT265/70R17E tires and 17- by 7.5-inch (ST) or 17- by 8-inch (SLT & Laramie) wheels (60-inch CA only; must have Cummins Turbo Diesel)	O	O	O
ST Décor Group – includes chrome front bumper and chrome grille surround with black billet inserts)	O	—	—
Trailer Tow Prep Group – includes trailer brake controller jumper harness	O	O	O
Light Group – includes under-hood lamp, ashtray lamp, switchable dome lamp, vanity mirror lamp for driver and passenger, auto day/night rearview mirror	—	O	—
Heavy-duty Snow Plow Group (4WD only) – includes transfer case skid plate and 160-amp alternator	O	O	O

Legend: S = Standard; O = Optional; L= Fleet only limited production option;

P = Available within package or group; — = Not available

2008 Dodge Ram 3500 Chassis Cab

SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Style	Chassis Cab
Assembly Plants	Saltillo, Coahuila, Mexico
EPA Vehicle Class	Medium Heavy Duty

ENGINE: 5.7-LITER HEMI® V-8

Availability	Standard
Type and Description	Eight-cylinder, 90° V-type, liquid-cooled
Displacement	343 cu. in. (5654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	Pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	9.6:1
Power (SAE net)	330 bhp (246 kW) @ 5,400 rpm (57.9 bhp/L)
Torque (SAE net)	375 lb.-ft. (509 N•m) @ 4,200 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2—recommended Unleaded regular, 87 octane (R+M)/2—acceptable
Oil Capacity	7 qt. (6.6L)
Coolant Capacity	18.7 qt. (17.7L)
Emission Control	Dual three-way catalytic converters, internal engine features with knock sensors

ENGINE: 6.7-LITER HIGH OUTPUT CUMMINS TURBODIESEL I-6

Availability	Optional
Type and Description	Six-cylinder, inline, liquid-cooled, turbocharged, intercooled
Displacement	408 cu. in. (6690 cu. cm)
Bore x Stroke	4.21 x 4.88 (107mm x 124mm)
Valve System	OHV, 24 valves, and solid lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Cast-iron block and head
Compression Ratio	17.3:1
Power (SAE net)	305 bhp (227 kW) @ 3,000 rpm—high output
Torque (SAE net)	610 lb.-ft. (827 N•m) @ 1,600 rpm—high output
Maximum High-Idle Engine Speed	3,500 rpm
Fuel Requirement	Ultra-low sulfur diesel

Oil Capacity	(Low ash req.) 12 qt. (11.3L) with filter
Coolant Capacity	32.7 qt. (30.9L)
Emission Controls	Oxidation catalytic converter w/after treatment system— internal engine features

ELECTRICAL SYSTEM

Alternator

Availability	Standard
Rating	136-amp
Battery	Maintenance-free, 750 CCA

Availability	Optional—all
Rating	160-amp
Battery	Maintenance-free, 750 CCA

Availability	Optional—with diesel engine
Rating	220-amp
Battery	Dual, maintenance-free, 750 CCA

Battery

Availability	Standard
Description	Group 65, maintenance-free, 750 CCA

Availability	Optional — with diesel engine
Description	Dual, Group 65, maintenance-free, 750 CCA

TRANSMISSION: G56-MANUAL, SIX-SPEED OVERDRIVE

Availability	Standard—all
Description	Synchronized in all gears
PTO Capable (35 HP max)	Six-bolt mounting, left side

Gear Ratios

1 st	5.94
2 nd	3.28
3 rd	1.98
4 th	1.3
5 th	1
6 th	0.74
Reverse	5.42

TRANSMISSION: 545RFE-AUTOMATIC FIVE-SPEED

Availability	Optional with 5.7L engine
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1 st	3
2 nd	1.67-upshift; 1.50-kick-down
3 rd	1
4 th	0.75
5 th	0.67
Reverse	3
Overall Top Gear	2.50 with 3.73 axle ratio; 2.63 with 4.10 axle ratio

TRANSMISSION: AISIN AS68RC SIX-SPEED

Availability	Optional with Cummins diesel engine
PTO Capable (35 HP max)	Six-bolt mounting; right side
Description	Electronically controlled overdrive lockout Electronically controlled converter clutch
Gear Ratios	
1 st	3.74
2 nd	2.00
3 rd	1.34
4 th	1
5 th	0.77
6 th	0.63
Reverse	3.54
Overall Top Gear Ratio	2.42 with 3.73 axle ratio; 2.67 with 4.10 axle ratio

TRANSFER CASE: NV273 (NV 271)

Availability	Standard 4x4
Type	Part-time
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Shift Mechanism	NV 273—electric (NV 271 manual)
Low-range Ratio	2.73
Center Differential	None

DIMENSIONS AND CAPACITIES

	3500 – SRW 60-inch cab-axle	3500 – DRW 60-inch cab-axle	3500 – DRW 84-inch cab-axle
Regular Cab—2WD			
Wheelbase	143.8	143.8	167.5
Track, Front	68.7	69.6	69.6

Track, Rear	68.1	71.7	71.7
Overall Length	234.3	234.3	258.3
Overall Width @ SgRP Front.	79.5	79.5	79.5
Overall Height	78.6	78.7	78.6
Suspension or Axle to Ground			
Front	8.3	8.5	8.5
Rear	7.4	7.6	7.6
Approach Angle	24.5°	24.8°	24.9°
Ramp Breakover Angle	21.6°	22°	20.5°
Departure Angle	21.8°	22°	21.8°
Fuel Tank, gal. (L)	Standard: 52 (197) rear Optional: 22 (83) side	Standard: 52 (197) rear Optional: 22 (83) side	Standard: 52 (197) rear Optional: 22 (83) side

Regular Cab—4WD

Wheelbase	143.8	143.8	167.5
Track, Front	68.7	69.6	69.6
Track, Rear	68.1	71.7	71.7
Overall Length	234.3	234.3	258.3
Overall Width @ SgRP Front	79.5	79.5	79.5
Overall Height.	78.6	78.7	78.6
Suspension or Axle to Ground			
Front	8.1	8.2	8.2
Rear	7.4	7.6	7.6
Approach Angle	24.5°	24.8°	24.9°
Ramp Breakover Angle	21.6°	22°	20.5°
Departure Angle	21.8°	22°	21.8°
Fuel Tank, gal. (L)	Standard: 52 (197) rear Optional: 22 (83) side	Standard: 52 (197) rear Optional: 22 (83) side	Standard: 52 (197) rear Optional: 22 (83) side

Quad Cab—2WD

Wheelbase	163.5	163.5
Track, Front	68.7	69.6
Track, Rear	68.1	71.7
Overall Length	254.3	254.3
Overall Width @ SgRP Front	79.5	79.5
Overall Height.	79	79.1
Suspension or Axle to Ground		
Front	8.3	8.5
Rear	7.4	7.6
Approach Angle	24.6°	24.9°
Ramp Breakover Angle	20.4°	20.7°
Departure Angle	21.5°	21.8°
Fuel Tank, gal. (L)	Standard: 52 (197) rear	Standard: 52 (197) rear

	Optional: 22 (83) side	Optional: 22 (83) side
Quad Cab—4WD		
Wheelbase	163.5	163.5
Track, Front	68.7	69.6
Track, Rear	68.1	71.7
Overall Length	254.3	254.3
Overall Width @ SgRP Front	79.5	79.5
Overall Height.	79	79.1
Suspension or Axle to Ground		
Front	8.1	8.2
Rear	7.4	7.6
Approach Angle	24.6°	24.9°
Ramp Breakover Angle	20.4°	20.7°
Departure Angle	21.5°	21.8°
Fuel Tank, gal. (L)	Standard: 52 (197) rear Optional: 22 (83) side	Standard: 52 (197) rear Optional: 22 (83) side

ACCOMMODATIONS		
	Regular Cab	Quad Cab
Seating Capacity, F/R	3/—	3/3
Front		
Head Room	40.8	41
Leg Room	41	41
Shoulder Room	67	67
Hip Room	65	65
Seat Travel	7.1	7.1
Rear		
Head Room	N/A	40
Leg Room	N/A	36.7
Shoulder Room	N/A	66.5
Hip Room	N/A	65.3
Knee Clearance	N/A	0.7
Interior Volume		
Front	64.8	65.1
Rear	N/A	56.6

2008 DODGE RAM 3500 CHASSIS CAB ESTIMATED PAYLOAD & TRAILER TOWING CAPACITIES

Ram 3500 Chassis Cab—2WD Quad Cab Single-Rear-Wheel (DC3L43)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
6.7L TD Diesel	M6	6-spd Manual	3.73	10,200	3690	6514	4060	2454	5200	6200	21,000	14,350
6.7L TD Diesel	M6	6-spd Manual	4.10	10,200	3690	6514	4060	2454	5200	6200	23,000	16,350
6.7L TD Diesel	A6	6-spd Auto	4.10	10,200	3660	6535	4079	2456	5200	6200	23,000	16,300

Ram 3500 Chassis Cab—2WD Quad Cab Dual-Rear-Wheel (DC3L43)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6430	6071	3325	2746	5200	9350	19,000	12,800
5.7L V-8 OHV Gas	A5	6-spd Auto	4.10	12,500	6410	6087	3339	2748	5200	9350	17,000	10,750
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5680	6818	4099	2719	5200	9350	21,000	14,050
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5680	6818	4099	2719	5200	9350	23,000	16,050
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5660	6840	4118	2722	5200	9350	23,000	16,000

DODGE RAM 3500 TOWING CAPACITIES**Ram 3500 Chassis Cab—2WD Regular Cab Single-Rear-Wheel (DC3L63)**

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
6.7L TD Diesel	M6	6-spd Manual	3.73	10,200	3950	6249	4008	2241	5200	6200	21,000	14,600
6.7L TD Diesel	M6	6-spd Manual	4.10	10,200	3950	6249	4008	2241	5200	6200	23,000	16,600
6.7L TD Diesel	A6	6-spd Auto	4.10	10,200	3930	6270	4027	2244	5200	6200	23,000	16,600

Ram 3500 Chassis Cab—2WD Regular Cab Dual-Rear-Wheel (DC3L63)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6650	5854	3156	2698	5200	9350	19,000	13,000
5.7L V-8 OHV Gas	A5	5-spd Auto	4.10	12,500	6630	5870	3170	2700	5200	9350	17,000	11,000
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5950	6553	4047	2507	5200	9350	21,000	14,300
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5950	6553	4047	2507	5200	9350	23,000	16,300
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5930	6575	4066	2509	5200	9350	23,000	16,300

DODGE RAM 3500 TOWING CAPACITIES**Ram 3500 Chassis Cab—2WD Regular Cab Dual-Rear-Wheel (DC3L64)**

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6510	5985	3298	2688	5200	9350	19,000	12,850
5.7L V-8 OHV Gas	A5	5-spd Auto	4.10	12,500	6500	6001	3311	2690	5200	9350	17,000	11,000
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5720	6783	4112	2671	5200	9350	21,000	14,150
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5720	6783	4112	2671	5200	9350	23,000	16,150
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5700	6805	4131	2674	5200	9350	23,000	16,150

Ram 3500 Chassis Cab—4WD Quad Cab Single-Rear-Wheel (DC8L43)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
6.7L TD Diesel	M6	6-spd Manual	3.73	10,200	3380	6821	4323	2499	5200	6200	21,000	14,050
6.7L TD Diesel	M6	6-spd Manual	4.10	10,200	3380	6821	4323	2499	5200	6200	23,000	16,050
6.7L TD Diesel	A6	6-spd Auto	4.10	10,200	3350	6851	4349	2502	5200	6200	23,000	16,000

DODGE RAM 3500 TOWING CAPACITIES**Ram 3500 Chassis Cab—4WD Quad Cab Dual-Rear-Wheel (DC8L43)**

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6060	6436	3596	2840	5200	9350	19,000	12,400
5.7L V-8 OHV Gas	A5	5-spd Auto	4.10	12,500	6040	6456	3613	2843	5200	9350	17,000	10,400
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5380	7125	4361	2764	5200	9350	21,000	13,750
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5380	7125	4361	2764	5200	9350	23,000	15,750
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5350	7155	4387	2768	5200	9350	23,000	15,700

Ram 3500 Chassis Cab—4WD Regular Cab Single-Rear-Wheel (DC8L63)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
6.7L TD Diesel	M6	6-spd Manual	3.73	10,200	3610	6587	4185	2402	5200	6200	21,000	14,250
6.7L TD Diesel	M6	6-spd Manual	4.10	10,200	3610	6587	4185	2402	5200	6200	23,000	16,250
6.7L TD Diesel	A6	6-spd Auto	4.10	10,200	3580	6617	4211	2406	5200	6200	23,000	16,250

DODGE RAM 3500 TOWING CAPACITIES**Ram 3500 Chassis Cab—4WD Regular Cab Dual-Rear-Wheel (DC8L63)**

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6420	6079	3377	2702	5200	9350	19,000	12,700
5.7L V-8 OHV Gas	A5	5-spd Auto	4.10	12,500	6400	6098	3393	2705	5200	9350	17,000	10,850
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5580	6920	4223	2698	5200	9350	21,000	14,000
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5580	6920	4223	2698	5200	9350	23,000	16,000
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5550	6950	4249	2701	5200	9350	23,000	16,000

Ram 3500 Chassis Cab—4WD Regular Cab Dual-Rear-Wheel (DC8L64)

Engine	Trans Type	Transmissio n	Axle Ratio	GVWR	Payload	Base Wt. Tot.	Base Wt. Ft.	Base Wt. R	GAWR Frt.	GAWR Rear	GCWR	Max. Trail
5.7L V-8 OHV Gas	M6	6-spd Manual	4.10	12,500	6090	6408	3716	2691	5200	9350	19,000	12,600
5.7L V-8 OHV Gas	A5	5-spd Auto	4.10	12,500	6070	6427	3733	2694	5200	9350	17,000	10,750
6.7L TD Diesel	M6	6-spd Manual	3.73	12,500	5430	7071	4358	2713	5200	9350	21,000	13,950
6.7L TD Diesel	M6	6-spd Manual	4.10	12,500	5430	7071	4358	2713	5200	9350	23,000	15,950
6.7L TD Diesel	A6	6-spd Auto	4.10	12,500	5400	7101	4384	2717	5200	9350	23,000	15,950